

TODA Flushing Oil

Product Descriptions

TODA Flushing Oil is high-quality oil products that have the ability to wash and clear out dirt in engines. It can be used for cleaning all types of engines.

Applications

- Take old engine oil out of the engine.
- Add TODA Flushing Oil before replacing the engine oil and oil filter. Start your engine for about 5-10 minutes. TODA Flushing Oil is thoroughly cleaned inside the engine, including valves and pistons.
- Take TODA Flushing Oil and oil filter out of the engine.
- Add new TODA engine oil into the engine.

Remark

- Do not accelerate or drive while using TODA Flushing Oil.
- The amount of TODA Flushing Oil used is equal to the oil change as usual.

Typicals

Density @15 °C, kg/l	0.87
Viscosity @40 °C mm ² /s	30
Pour Point, °C	-15
Flash Point COC, °C	214
Total Sulphur, mg/kg	<10

Packing Size 1 liter, 4 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com