

TODA Diesel 15W-40

Product Descriptions

TODA Diesel 15W-40 is a premium and high-quality lubricant formulated to exceed API CF-4/SJ which is the highest diesel engine lubricant standard. It is formulated from selected quality base oil and outstanding additive.

Quality Attributes

- Anti-oxidation performance to fight sludge build-up and preserve diesel engine efficiency
- Helps to reduce leaks in older
- Low sulphated Ash, Phosphorus, and Sulphur technology to protect exhaust after-treatment devices in new diesel engines
- Superb resistance to corrosive and abrasive wear
- Excellent oil consumption control

Applications

- Suitable for petrol and diesel engines both with and without turbochargers, under all operating conditions in all seasons.

Specifications

API CF-4/SJ

Typicals

Density @15 °C, kg/l	0.87
Viscosity @40 °C mm ² /s	108
Viscosity @100 °C mm ² /s	14.8
Viscosity Index	142
Pour Point, °C	-27
Flash Point COC, °C	244
Total Base Number, mgKOH/g	7.2

Packing Size 1 liter, 6 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com